



Specifications

DTP T FB 232

Video

VGA

Gain	Unity
Bandwidth.....	170 MHz (-3 dB)
Crosstalk	-50 dB @ 10 MHz, -30 dB @ 100 MHz
Switching speed.....	<5 ms. (max)

HDMI

Maximum data rate	6.75 Gbps (2.25 Gbps per color)
Maximum pixel clock	165 MHz
Resolution range	Up to 1920x1200 or 1080p @ 60 Hz; 2k
Formats.....	RGB and YCbCr digital video
Standards.....	DVI 1.0, HDMI, HDCP 1.1, CEA-861E

Video input – HDMI

Number/signal type.....	1 HDMI input (or single-link DVI-D with the appropriate DVI-HDMI adapters)
Connectors	1 female HDMI type A

Video input – VGA

Number/signal type.....	1 VGA-QXGA; RGBHV
Connectors	1 female 15-pin HD
Nominal level.....	0.7 Vp-p for RGB
Min./max. level.....	Analog, 0.3 V to 1.5 Vp-p with no offset
Impedance.....	75 ohms
Horizontal frequency	15 kHz to 145 kHz
Vertical frequency.....	30 Hz to 170 Hz
Return loss	<-40 dB @ 5 MHz

NOTE: The VGA input is digitized and output as DTP. The VGA signal is not scaled.

Sync – VGA

Input type	RGBHV
Input level	1.9 V to 5.0 Vp-p
S/N.....	>90 dB at maximum input (unweighted)
Max. input voltage.....	5.0 Vp-p

Interconnection between transmitter and receiver

Number/signal type.....	1 DTP 230 output
Connector.....	1 female RJ-45
Termination standard.....	TIA/EIA T568B
Transmission distance.....	Up to 230' (70 m) using shielded twisted pair cable or XTP DTP 24 STP cable
Cable requirements	Solid conductor, 24 AWG or better
Cable recommendations.....	400 MHz bandwidth, STP (shielded twisted pair)

NOTE: Extron XTP DTP 24 shielded twisted pair cable is strongly recommended for optimal performance.

NOTE: Input and output mode signaling:

DTP:	HDMI with embedded audio, analog audio, RS-232 and IR, and remote power
HDBaseT:	HDMI with embedded audio plus RS-232 and IR

Specification • DTP T FB 232 (Continued)

Audio

Gain.....	Unbalanced output: 0 dB; balanced output +6 dB
Frequency response	20 Hz to 20 kHz, ± 0.5 dB
THD + Noise.....	0.01% @ 1 kHz at nominal level
S/N.....	>90 dB, at maximum input (unweighted)
Crosstalk	<-45 dB @ 20 kHz, or -72 dB @ 1 kHz or below
Stereo channel separation.....	>80 dB @ 1 kHz to 20 kHz

Audio input

Number/signal type.....	1 analog stereo, unbalanced or 1 digital audio, embedded in the HDMI
Connectors.....	1 female 3.5 mm mini stereo jack 1 female HDMI Type A (shared with video input)
Source formats	
HDMI.....	LPCM up to 7.1/24-bit/192 kHz, Dolby TrueHD, Dolby Digital Plus, Dolby Digital EX, Dolby Digital 5.1, Dolby Digital 2/0 Surround, Dolby Digital 2/0, DTS-HD Master Audio, DTS-HD, DTS-ES Discrete 6.1, DTS-ES Matrix 6.1, DTS Digital Surround 5.1, DTS 2 Channel
Analog.....	Analog stereo audio
Impedance.....	10k ohms, DC coupled
Nominal level.....	-10 dBV
Maximum level.....	+6dBV, unbalanced
CMRR.....	>60 dB typ @ 1 kHz
Input gain adjustment.....	-18 dB to +24 dB, 1 dB steps, adjustable per input

NOTE: 0 dBu = 0.775 Vrms, 0 dBV = 1 Vrms, 0 dBV \approx 2 dBu

Audio output

Number/signal type.....	1 analog audio over DTP signal, or 1 embedded digital audio over DTP signal
Connectors.....	1 RJ-45 jack

Communications – switcher

Serial control port.....	RS-232 via (1) 3.5 mm, 3 pole captive screw connector
Serial control pin configuration	Pin 1 = Tx, pin 2 = Rx, pin 3 = Gnd
Baud rate and protocol (RS-232) ...	9600 baud, 8 data bits, 1 stop bit, no parity
USB control port.....	1 female mini USB, type B
USB standards	USB 2.0, high speed
Program control.....	Extron Simple Instruction Set (SIS™)

Communications – RS-232/IR over TP

NOTE: Protocol is mirrored between the connected DTP 230 Rx and the Over TP output port. Signals from a control device pass into the Over TP port, are embedded with the DTP signal, and sent to the DTP 230 Rx endpoint for control of remote sink and source devices.
The Over TP port is a pass-through connection to the DTP endpoint. There is no RS-232 or IR insertion from the DTP T FB 232 control port to the Over TP port.

Serial control pass-through port.....	1 RS-232 and IR via (1) 3.5 mm, 5-pole captive screw connector
Serial control pin configuration	Pin 1 = Tx, pin 2 = Rx, pin 3 = Gnd
Baud rates.....	300 to 115200 baud
Protocol.....	8 or 7 data bits 1 or 2 stop bits no parity (default) even or odd parity
IR pass-through control port	TTL level (0 to 5 V) modulated infrared control from 30 kHz up to 60 kHz
IR control pin configuration	3 = GND, 4 = IR Tx, 5 = IR Rx

Specification • DTP T FB 232 (Continued)

General

Power supply	External Input: 100 to 240 VAC, 50-60 Hz Output: 12 VDC, 1 A, 12 watts
Power consumption	
Device	5.2 watts, 12 VDC
Device and power supply	6.4 watts, 100-240 VAC, 50-60 Hz
Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +104 °F (0 to +40 °C) / 10% to 90%, noncondensing
Cooling	Convection, no vents
Thermal dissipation	
Device	17.7 BTU/hr
Device and power supply	21.9 BTU/hr
Mounting	
Floor box mount	Ackermann GB3/OBO Betterman floor box, MK Electric CableLink Plus Single Pan floor box, MK Electric CableLink Plus Modular floor box, ElectraPlan floor box, and PUK floor box mountable

NOTE: See the *DTP T FB 232 User Guide* for mounting considerations.

Enclosure type	Metal
Enclosure dimensions	2.3" H x 2.8" W x 5.2" D* (5.9 cm H x 7.2 cm W x 13.2 cm D) (Dimensions exclude connectors) * Depth is 6.1" (15.5 cm) including mounting tabs
Product weight	1.1 lbs (0.5 kg)
Shipping weight	3 lbs (1.4 kg)
Vibration	ISTA 1A in carton (International Safe Transit Association)
Regulatory compliance	
Safety	CE, c-UL, UL
EMI/EMC	CE**, C-tick, FCC Class A**, ICES, VCCI
Environmental	Complies with the appropriate requirements of RoHS, WEEE.

NOTE: **CE and FCC testing is conducted with STP (shielded twisted pair) cable.

Warranty	3 years parts and labor
----------------	-------------------------

NOTE: All nominal levels are at ±10%.

NOTE: Specifications are subject to change without notice.

NOTE: Shipping weights and dimensions are available at www.extron.com.

CMS-103117-D9

Extron Headquarters +800.633.9876 Inside USA/Canada Only	Extron Europe +800.3987.6673 Inside Europe Only	Extron Asia +65.6383.4400 +65.6383.4664 FAX	Extron Japan +81.3.3511.7655 +81.3.3511.7656 FAX	Extron China +86.21.3760.1568 +86.21.3760.1566 FAX	Extron Middle East +971.4.299.1800 +971.4.299.1880 FAX	Extron Australia +61.8.8113.6800 +61.8.8351.2511 FAX	Extron India 1800.3070.3777 (Inside India Only) +91.80.3055.3777 +91.80.3055.3737 FAX
Extron USA - West +1.714.491.1500 +1.714.491.1517 FAX	Extron USA - East +1.919.850.1000 +1.919.850.1001 FAX	+31.33.453.4040 +31.33.453.4050 FAX					